



# Extreme CL2222 Waterproof Luminaire



## GENERAL INFORMATION

Operating Temperature	-20 °C / +50°C -40 °C / +70°C (optional)
Storage Temperature	-40°C / +80°C
Main Reference	EN 60598-1, EN 60598-2-1, EN 60529,
Company Standards	EN 62262, IES LM 80-15, ISO45001, ISO39001, EAC

## HOUSING AND MATERIALS

Housing	Polycarbonate (PC)
Gasket	Silicon or polyurethane without junction points.
Reflector	Powder painted sheet steel
Cable Gland	IP66, Plastic PG7, IP67 (optional), IP68 (optional)
Tightness Level	IP65
Impact Housing Resistance	IK08 (5 J)
Impact Glass Resistance	IK08 (5 J)
Vibration Test	Compliant with modified IEC 68-2-6 (0.5G), ANSI C136.31 (3G-5G)

## ELECTRICAL INFORMATION

Electrical Class	Class I, Class II (optional)
Nominal Voltage	220-240V 50 / 60 Hz EU 110-277V 50 / 60 Hz (optional) NORTH AMERICA
LED Current	250 mA, 300 mA, 350 mA, 500 mA, 600 mA
Power Factor	≥0.9 (at full load)
Driver	Constant current, thermal protected, voltage regulated, harmonic filter protection
Surge protection options (kV)	1 Kv (standard) 10 kV (optional) with LED signal and thermo fuse to disconnect load at the end of life
Emergency Kit (optional)	1 hour battery 3 hours battery
Control system	on-off (standard), Bluetooth, DALI, 1-10V DIM, stand alone automation
Sensor	PIR (optional), Photocell (optional),
Mains connection	For cable max section 2,5 mm <sup>2</sup> Outgoing cable H05RN-F 2/3/5 x 1,5 mm <sup>2</sup> Length on request.(optional)
Electromagnetic compatibility (EMC)	IEC 61000, EN 55015, IEC 61000-3-2, IEC 61000-4-5, IEC 61547, IEC 61000-3-3, IEC 61000-4-2, IEC 61000-2-2, IEC 61000-4-11, IEC 61643-11

## OPTICAL INFORMATION

LED colour temperature	3000K (warm white) 4000K (neutral white) (standard) 5000K (cool white) 6500K (cool white)
Colour rendering index (CRI)	CRI ≥80 CRI ≥90 (optional)
Upward light output ratio	0%
Photobiological safety class	IEC 62471, EN 62778 EXEMPT GROUP
Testing standard	LM 79-19, EN 13032-1 (all measurements in ISO17025 accredited laboratory)
Lifetime of the LEDs	Tq= 25 °, 700 Ma ≥ 100.000h -L70 Tq= 55 °, 700 Ma ≥ 100.000h -L70



www.cemdag.com  
cemdag@cemdag.com

+90 232 444 4 236  
CEM

# Extreme CL2222

## Waterproof Luminaire



Power	Luminaire Output Flux (lm)		W (mm)	L (mm)	h (mm)	Item / Box	Average Weight (kg)	Order Code	System Lumen / W (lm)	
	max.	min.							max.	min.
20W	2400	1800	77	560	70	1	2.00	L2222-LED0020NW-ECG	120	90
30W	3600	2700	77	560	70	1	2.00	L2222-LED0030NW-ECG	120	90
36W	4320	3240	77	560	70	1	2.00	L2222-LED0036NW-ECG	120	90
30W	3600	2700	77	1000	70	1	2.00	L2222-LED0130NW-ECG	120	90
36W	4320	3240	77	1000	70	1	2.00	L2222-LED0136NW-ECG	120	90
40W	5040	3780	77	1000	70	1	2.00	L2222-LED0140NW-ECG	120	90

Depending on the luminaire configuration. For more details, please contact us.  
Tolerance on LED flux is +/-7% and on total luminaire power +/- 5%.


### Main Applications



Dust and Moisture Industries   Warehouses   Chemical Industries   Textile Factories   Garages   Tunnels   Subways   Horticulture



Greenhouses   Shipyards



[www.cemdag.com](http://www.cemdag.com)  
cemdag@cemdag.com

Cemdag reserve the right to modify design and/or production characteristics of their products. photographs and data used in this catalogue are for illustrative purposes are not binding on the company.

+90 232 **444 4 236**  
**CEM**

The copying or reproduction, in part or in full, of any descriptions, technical data drawings or photographs shown in this catalogue is expressly forbidden.

